

CELDUC France, Momentanschaltende Halbleiterrelais

Reference	Max. switching current	Max. switching voltage	Control voltage	Specification
SO745090	50A	12-275VAC	3-32VDC	Random
SO747090	75A	12-275VAC	3-32VDC	Random
SO763090	35A	24-510VAC	3,5-32VDC	Random
SO765090	50A	24-510VAC	3,5-32VDC	Random
SO767090	75A	24-510VAC	3,5-32VDC	Random
SO768090	95A	24-510VAC	3,5-32VDC	Random
SO769090	125A	24-510VAC	3,5-32VDC	Random
SC741110	12A	12-280VAC	3-30VDC	Random
SC742110	25A	12-280VAC	3-30VDC	Random
SC744110	40A	12-280VAC	3-30VDC	Random
SC762110	25A	24-520VAC	4-30VDC	Random
SC764110	50A	24-520VAC	4-30VDC	Random
SC764910	50A	24-520VAC	90-240VAC	AC random output
SC767110	75A	24-520VAC	4-30VDC	Random
SC768110	95A	24-520VAC	4-30VDC	Random
SC769110	125A	24-520VAC	4-30VDC	Random
SOL745060	50A	12-280VAC	3-32VDC	Random
SU765070	50A	24-510VAC	3,5-32VDC	Random